

# THAYER

- NEW MACHINERY
- USED MACHINERY
- TOOLING

**Since  
1946**

**email: [machinery@wwthayer.com](mailto:machinery@wwthayer.com)  
[www.thayerused.com](http://www.thayerused.com)**

**1444 Hoelzer Court  
Pacific, MO 63069**

DISTRIBUTOR OF PROFIT PRODUCING WOODWORKING MACHINERY AND TOOLING

**TOLL FREE (800) 323-7430  
(636) 257-3311**



## Holz Her 7123K Point to Point Machine Center

Machine: Point to Point Machine Center  
Brand: Holz Her  
Model Number: 7123K  
Year of Manufacture: 2005

- Work area capacity of 3200mm (125") x 1585mm (62") with (6) movable panel support benches. (10) full sized pods 135mm x 110mm (5-1/2" x 4-1/4") and (4) narrow pods 125mm x 75mm (5" x 4-1/4"). working zones makes it possible to load the machine with (2) work pieces at a time, 36" working height
- Vertical Router - Motor 12 KW- (16 HP), fully programmable from 1,000 to 24,000 RPM, HSK-63F
- Boring Unit - (24) Spindles consisting of (18) Vertical and (6) Horizontal. VERTICAL spindles - (10) in X axis and (8) in Y axis on 32mm centers. HORIZONTAL spindles - (2) Double spindles in X axis and (1) Double spindle in Y axis. All spindles individually activated, takes standard boring bits - 70mm long, with 10mm diameter smooth shanks. The boring gear box is driven by a 3.6 KW (5 HP) motor, fully programmable from 1000 to 6800 RPM
- Head travels on linear motion guides - Maximum rapid traverse X axis 100m/minute (3900 inches/minute) driven by helical gear; maximum rapid traverse Y axis 100m/minute (3900 inches/minute) driven by ball screw; Z axis 25m/minute (975 inches/minute) driven by ball screw
- (12) Position Automatic Tool Changer (HSK-63F type)
- Safety - perimeter fence helps prevent accidental intrusion from the ends or back of the machine. Safety mats assist in stopping the machine if operator enters the working area while the machining head is in operation. The mats are divided into (2) working zones so you may load or unload parts at one end of the machine while the machine continues to work on the opposite end
- TwinCAM 32 user software with graphical user interface - Features a Personal computer control with 15" screen, (1) diskette drive, (1) CD-ROM drive, PC-compatible US keyboard and mouse, barcode reader, Windows operating system
- Nash Elmo 2.4/3.5 KW Vacuum pump
- Dongan 34 KVA Transformer - 230 Volt primary, 400/230 secondary
- 250mm (9-3/4") Dust Hood

FOB Pacific, MO

Machine specifications are based on original manufacturer's information and are subject to verification. Equipment is subject to prior sale without notice. Prices quoted do not include any sales or use tax. Carting of used machinery is not included.